



DM2H2036

Model NO.		DM2H2036
Camera		
Image Sensor		IMX322
Main processor		HI3516C
Resolution		1080P
Effective Pixels		1920(H)*1080(V)
TV System		PAL/NTSC
Electronic Shutter Time		Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
S/N Ratio		≥52dB
Scanning System		Progressive
Video Output		Network
Lens		
Focus Length		Board Lens 3.6mm/F2.0
Focus Control		Fixed
Lens Type		Fixed
Pixels		2M Pixels
Night Vision		
Infrared LED		12μ x 12PCS
Infrared Distance		20M
IR Status		Under 10 Lux By CDS
IR Power On		CDS Auto Control
Network		
Ethernet		RJ-45 (10/100Base-T)
Protocol		IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF		Support ONVIF 2.4
P2P		YES, Support QR Code
POE		Optional, Support IEEE 802.3af
WIFI		N/A
Video Delay		0.3S (Within the Lan)
Main Stream		1920*1080 & 1280*720 @25fps
Sub Stream		720*480@25fps
IE Brower		IE6-11, Google Chrome(IE Tab), Firefox(IE Tab)
Smart Phone		iPhone, iPad, Android, Android Pad
Camera Features		
Day/Night		Color/ B&W (IR-CUT)
Compression		H.264/JPEG/AVI
Image Config		Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection		Support
Privacy Masking		3 Rectangular Zone
WDR		YES
Recording Mode		NVR/NAS/CMS/Web
Language		Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
General		
Housing		metal
Anti-cut Bracket		NO
IR Cut Filter		YES
Operation Temperature		-10 ~ +50 RH95% Max
Storage Temperature		-20 ~ +60 RH95% Max
Power Source		DC12V±10%, 500mA
Dimension		95.5(W) x 95.5(H) x 62(D)mm
Weight		289g