



DM3A2060

Model NO.	DM3A2060
Camera	
Image Sensor	IMX322
Main processor	HI3516C
Resolution	1080P
Effective Pixels	1920(H)*1080(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Lens	
Focus Length	Board Lens 6mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels
Night Vision	
Infrared LED	18.5μs 2PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.35 (Within the Lan)
Main Stream	1920*1080 & 1280*720 @25fps
Sub Stream	720*480@30fps
IE Brower	IE6-11, Google Chrome(IE Tab), Firefox(IE Tab)
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/JPEG/AVI
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	YES
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
General	
Housing	Metal
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-10 ~ +50 RH95% Max
Storage Temperature	-20 ~ +60 RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	∅ 120x 100(H) mm
Weight	800g